

AGRICULTURAL & OFF-THE-ROAD TIRES




HEAD OFFICE
15F Mingzuo Mansion
No.111 Haibin
North Road
Weihai
China

T. +86 (0)631 5217918
E. lisa.z@barkleytire.com
E. sebastiaan@barkleytire.com



barkleytire.com



**DELIVERING PERFORMANCE
DRIVING GROWTH**



CONTENTS

ABOUT BARKLEY	4	BXL TRAC PRO	32
TRACTORS 	8	BXL PROTECT PRO	32
AGRI EVERLAST 01	8	BLB07S+	33
AGRI EVERLAST 01	9	BLB06S+	33
AGRI EVERLAST 01	9	BXA PROTO	34
BLA01	10	BLA06	34
BLA02	12	ADT&SCRAPER 	35
BLA03	13	BXA PROTO	35
HARVESTERS 	14	BXA MASTER PRO	35
BLA05	14	BLM06S	36
BLA07	15	SAND 	36
AGRI HARVEST BLA09	16	BXF MASTER PRO	36
SPRAYERS 	17	MOBILE CRANE 	37
BLA01	17	BXC MASTER PRO	37
BLA08	17	CRANE PROTO	37
FLOATERS 	18	RIGID DUMP TRUCKS 	38
BLAF1	18	BLDUMP 44+	38
BLF01	19	BLDUMP 66+	38
INDUSTRIAL 	20	BLDUMP 68	39
BLA04	20	BLDUMP 68+	39
BLA06	21	BLDUMP 33+	40
LL309	21	BLDUMP 36+	40
TRAILERS 	22	BLDUMP 69+	41
BLT03	22	BLDUMP 98+	41
BL606	23	BLDUMP TRAC	42
IMPLEMENT 	24	BLROCK PROTO	42
BBAF2	24	BXD MASTER PRO	43
BBAF1E	25	BLB02S	43
LOADERS&DOZERS 	28	UNDERGROUND MINE 	44
BXL MASTER PRO	28	LHD MASTER PRO	44
BXL PRO	28	LHD PROTO	44
BLB01	29	HEAVY TRUCK 	45
BLB05S	29	BXF PROTO	45
BXS MASTER PRO	30	BXF EXTREME	45
BLS09	30	BLM05	46
BXG MASTER PRO	31	ROLLER 	46
BLGRADER PRO+	31	LL308	46



TRUCK & BUS

AGRICULTURE

OFF-THE-ROAD

ABOUT BARKLEY

Count on the best price per kilometer, count on Barkley. Enjoy best value tires, expertly crafted in Europe & Asia. With fast delivery and low minimum order quantities, backed by our knowledgeable support.

In today's economic landscape, the significance of price and value resonates deeply with all of us, alongside an unwavering commitment to quality and safety.

At Barkley, we stand firm in our pledge to deliver high-quality tires at competitive prices, ensuring that every purchase represents both value and reliability.

Our customers take pride in our products, finding satisfaction in the craftsmanship and dedication that

goes into each tire we produce. Moreover, we prioritise equipping you with the professional knowledge necessary to make informed decisions about your tire needs.

We consider our customers part of the Barkley family, providing steadfast support and guidance every step of the way as you navigate through the myriad of options to find the perfect tires for your business.

DELIVERING PERFORMANCE DRIVING GROWTH



AGRICULTURAL TIRES

High load-bearing capacity, excellent quality and wide modern pattern with superb self-cleansing properties.



OFF-ROAD TIRES

Strong, flexible shock absorbing tires that improve drive comfort and provide lower fuel consumption.



CONSISTENT QUALITY

We work with carefully selected manufacturers offering consistent quality across our ranges.



LOW MINIMUM ORDERS

We offer lower minimum order quantities at very competitive prices, direct to your door.



EXPERT SUPPORT

We provide ongoing technical support and knowledgeable guidance to all of our customers.



FACTORY VISITS

Get in touch to arrange a guided tour around our factories in either Serbia, Thailand or China.

High load-bearing capacity, excellent quality and a wide modern pattern with superb self-cleansing properties!

Fertilising, sowing, harvesting, ploughing, tractor tires must meet strict requirements because they deal with all kinds of conditions.

Our tires will help you to maximise the potential of your harvest. By using top quality tires at a very competitive price! Technology never stands still. Certainly when it comes to Agriculture. Stronger, faster and heavier tractors that must travel long distances on roads at higher speeds. Naturally, your tractor tires must also deal with these new demands. We can offer you tires with the traction, life-span and soil protection you are looking for. Like the BLA07 - our large-volume tire for tractors.



AGR/
AGRICULTURAL





AGRI EVERLAST 01

- ✓ With advanced lug and tread designs that help to provide maximum traction and good self-cleaning properties
- ✓ Large contact area results in low surface pressure and minimal soil compaction
- ✓ Exclusive rubber compound for added durability against chipping from stubble



Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
380/85R28	133/130	A8/B	R-1W	W11 W12 W13	380	1357	2060	160	42	TL
420/85R24	149/146	A8/B	R-1W	W13 W14L W15L	418	1324	3250	340	46	TL
420/85R28	144/144	A8/B	R-1W	W13 W14L W15L	418	1425	2800	240	46	TL
460/85R38	149/146	A8/B	R-1W	W14L W15L W16L	455	1747	3250	160	49	TL
520/85R38	160/160	A8/B	R-1W	DW16L DW18L	516	1849	4500	240	51.5	TL



AGRI EVERLAST 02

- ✓ With advanced lug and tread designs that help to provide maximum traction and good self-cleaning properties
- ✓ Large contact area results in low surface pressure and minimal soil compaction
- ✓ Exclusive rubber compound for added durability against chipping from stubble



Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
480/70R24	155/158	D/A8	R-1W	W14L W15L W16L	479	1316	3875	420	47	TL



AGRI EVERLAST 03

- ✓ Extra wide footprint provides premium respect for the soil, enhancing farm productivity and increasing crop yield
- ✓ Strong and well-engineered casings make it possible to deal with the heaviest loads without compromising your operation speed
- ✓ Modern lug design delivers an exceptionally smooth ride on the road up to 65km/h



Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
540/65R30	150/153	D/A8	R-1W	W16L W18L	550	1464	3350	240	48	TL
650/65R42	170	D	R-1W	DW20B DW21B DW23B	645	1913	6000	320	53.5	TL

BLA01

- ✓ Deep lugs, low slip and optimized rubber compounds help reduce wear for exceptionally long tire life
- ✓ Good self-cleaning properties help keep the tread pattern free of mud, resulting in less slip, even in difficult conditions
- ✓ Multiple types of rubber are designed with tread compound, providing excellent wear and fatigue resistance



Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
280/85R24	115/112	A8/B	R-1W	W9 W10	282	1086	1215	160	39	TL
320/85R24	122/119	A8/B	R-1W	W9 W10 W11	319	1154	1500	160	41	TL
	139/139	A8/B	R-1W	W9 W10 W11	319	1154	2430	280	41	TL
320/85R28	124/121	A8/B	R-1W	W9 W10 W11	319	1255	1600	160	41	TL
320/85R32	142/139	A8/B	R-1W	W9 W10 W11	319	1357	2650	400	41	TL
320/85R36	128/125	A8/B	R-1W	W9 W10 W11	319	1458	1800	160	41	TL
340/85R24	125/122	A8/B	R-1W	W11 W12	343	1188	1650	160	42	TL
340/85R28	127/124	A8/B	R-1W	W11 W12	343	1289	1750	160	42	TL
340/85R32	142/139	A8/B	R-1W	W11 W12	343	1391	2650	360	42	TL
340/85R36	132/129	A8/B	R-1W	W11 W12	343	1492	2000	160	42	TL
340/85R38	133/130	A8/B	R-1W	W11 W12	343	1543	2060	160	42	TL
380/85R24	131/128	A8/B	R-1W	W11 W12 W13	380	1256	1950	160	45	TL
380/85R28	133/130	A8/B	R-1W	W11 W12 W13	380	1357	2060	160	45	TL
380/85R30	135/132	A8/B	R-1W	W11 W12 W13	380	1408	2180	160	45	TL
380/85R34	147/147	A8/B	R-1W	W11 W12 W13	380	1510	3075	300	45	TL
420/85R24	137/134	A8/B	R-1W	W13 W14L W15L	418	1324	2300	160	48	TL

Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
420/85R28	139/136	A8/B	R-1W	W13 W14L W15L	418	1425	2430	160	48	TL
	144/144	A8/B	R-1W	W13 W14L W15L	418	1425	2800	240	48	TL
420/85R30	140/137	A8/B	R-1W	W13 W14L W15L	418	1476	2500	160	48	TL
	145/145	A8/B	R-1W	W13 W14L W15L	418	1476	2900	240	48	TL
420/85R34	142/139	A8/B	R-1W	W13 W14L W15L	418	1578	2650	160	48	TL
420/85R38	144/141	A8/B	R-1W	W13 W14L W15L	418	1679	2800	160	48	TL
460/85R30	145/142	A8/B	R-1W	W14L W15L W16L	455	1544	2900	160	51	TL
460/85R34	147/144	A8/B	R-1W	W14L W15L W16L	455	1646	3075	160	51	TL
460/85R38	149/146	A8/B	R-1W	W14L W15L W16L	455	1747	3250	160	51	TL
460/85R42	150/147	A8/B	R-1W	W14L W15L W16L	455	1849	3350	160	51	TL
460/85R46	158/155	A8/B	R-1W	W14L	464	1943	4250	240	51	TL
520/85R38	155/152	A8/B	R-1W	DW16L DW18L	516	1849	3875	160	54	TL
	160/160	A8/B	R-1W	DW16L DW18L	516	1849	4500	240	54	TL
520/85R42	157/154	A8/B	R-1W	DW16L DW18L	516	1951	4125	160	54	TL
	167/164	A8/B	R-1W	DW16L DW18L	516	1951	5450	320	54	TL
520/85R46	164/164	A8/B	R-1W	DW16L DW18L	516	2052	5000	240	55	TL
420/80R46	151/148	A8/B	R-1W	W12 W13	418	1840	3450	240	47	TL
480/80R42	156/156	A8/B	R-1W	DD16L DW16L W16L DW16A W16A	479	1835	4000	240	49	TL
480/80R46	158/158	A8/B	R-1W	DD16L DW16L W16L DW16A W16A	479	1936	4250	240	49	TL
420/90R30	147/144	A8/B	R-1W	DW13 W14L	418	1518	3075	240	48	TL
320/90R46	146/143	A8/B	R-1	W9 W10 W11	319	1744	3000	320	37	TL



BLA02

- ✓ Outstanding long tire life thanks to the use of a wear-resistant tread compound
- ✓ Super flat tread and large footprint help reduce soil compaction



Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
240/70R16	104/104	A8/B	R-1W	W8 W8L W9	244	742	900	240	27	TL
260/70R16	109/109	A8/B	R-1W	W8 W8L W9	258	770	1030	240	29	TL
280/70R16	112/112	A8/B	R-1W	W8 W8L W9 W10	282	798	1120	240	30	TL
280/70R20	116/113	A8/B	R-1W	W8 W8L W9 W10	282	900	1250	240	35.5	TL
320/70R20	113/113	A8/B	R-1W	W9 W10 W11	319	982	1150	160	36	TL
	137/137	A8/B	R-1W	W9 W10 W11	319	982	2300	400	36	TL
320/70R24	116/116	A8/B	R-1W	W9 W10 W11	319	1094	1250	160	38	TL
360/70R24	122/119	A8/B	R-1W	W10 W11 W12	357	1152	1500	160	42	TL
	127/124	A8/B	R-1W	W10 W11 W12	357	1152	1750	240	42	TL
380/70R24	125/125	A8/B	R-1W	W11 W12 W13	380	1190	1650	160	43	TL
420/70R24	130/127	A8/B	R-1W	W12 W13 W14L	418	1248	1900	160	44	TL
	136/133	A8/B	R-1W	W12 W13 W14L	418	1248	2240	240	44	TL
420/70R28	139/136	A8/B	R-1W	W12 W13 W14L	418	1349	2430	240	44	TL
480/70R24	138/135	A8/B	R-1W	W14L W15L W16L	479	1316	2360	160	47	TL
	140/137	A8/B	R-1W	W14L W15L W16L	479	1421	2500	160	47	TL
480/70R28	145/142	A8/B	R-1W	W14L W15L W16L	479	1421	2900	240	47	TL
	151/148	A8/B	R-1W	W14L W15L W16L	479	1421	3450	320	47	TL
480/70R34	143/143	A8/B	R-1W	W14L W15L W16L	479	1580	2725	160	47	TL
480/70R38	145/142	A8/B	R-1W	W14L W15L W16L	479	1681	2900	160	47	TL
520/70R38	150/150	A8/B	R-1W	W15L W16L W18L	516	1749	3350	160	48	TL
580/70R38	155/155	A8/B	R-1W	W18L	577	1827	3875	160	50	TL
	170/167	A8/B	R-1W	W18L	577	1827	6000	280	50	TL



BLA03

- ✓ The tread pattern ensures excellent self-cleaning
- ✓ Maximum traction and outstanding productivity thanks to a large contact patch
- ✓ Capable of comfortably working at speeds up to 65km/h



Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
440/65R24	128/131	D/A8	R-1W	W13 W14L W15L	441	1182	1800	160	45	TL
440/65R28	131/134	D/A8	R-1W	W13 W14L W15L	441	1283	1950	160	45	TL
480/65R24	133/136	D/A8	R-1W	W14L W15L	479	1234	2060	160	46	TL
480/65R28	136/139	D/A8	R-1W	W14L W15L	479	1335	2240	160	46	TL
540/65R24	140/143	D/A8	R-1W	W16L W18L	550	1312	2500	160	48	TL
540/65R28	142/145	D/A8	R-1W	W16L W18L	550	1413	2650	160	48	TL
540/65R30	150/153	D/A8	R-1W	W16L W18L	550	1464	3350	240	48	TL
540/65R34	145/148	D/A8	R-1W	W16L W18L	550	1566	2900	160	48	TL
540/65R38	153/156	D/A8	R-1W	W16L W18L	550	1667	3650	240	48	TL
600/65R28	147/150	D/A8	R-1W	DW20B W18L	591	1491	3075	160	52	TL
	154	D	R-1W	DW20B W18L	591	1491	3750	240	52	TL
600/65R34	157/160	D/A8	R-1W	DW20B W18L	591	1644	4125	240	52	TL
600/65R38	153/156	D/A8	R-1W	DW20B W18L	591	1745	3650	160	52	TL
650/65R38	157/160	D/A8	R-1W	DW20B	645	1811	4125	160	56	TL
650/65R42	165/168	D/A8	R-1W	DW20B	645	1913	5150	240	56	TL
710/70R38	166/169	D/A8	R-1W	DW23B	716	1959	5300	160	57	TL
	171	D	R-1W	DW23B	716	1959	6150	240	57	TL
710/70R42	168/171	D/A8	R-1W	DW23B	716	2061	5600	160	57	TL
	173/176	D/A8	R-1W	DW23B	716	2061	6500	240	57	TL



BLA05

- ✓ Outstanding long tire life thanks to the use of a wear-resistant tread compound
- ✓ Super flat tread and large footprint help reduce soil compaction



Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
650/75R32	172/172	A8/B	R-1W	DW20B DW21B DW23B	645	1789	6300	320	59	TL
710/60R34	164/167	D/A8	R-1W	DW21B DW23B DW24B DW25B	716	1716	5000	240	58	TL
750/65R26	171/171	A8/B	R-1W	DW23B DW24B DW25B	754	1636	6150	320	50	TL
VF 750/65R26 CFO	177	A8	R-1W	DW23B DW24B DW25B	754	1636	7300	240	50	TL
800/70R32	181/181	A8/B	R-1W	DW25B DW27B DH27B	798	1933	8250	320	57	TL
800/65R32	181/181	A8/B	R-1W	DW25B DW27B DH27B	798	1853	8250	360	58	TL



BLA07

- ✓ The tread pattern ensures excellent self-cleaning
- ✓ Maximum traction and outstanding productivity thanks to a large contact patch
- ✓ Capable of comfortably working at speeds up to 65km/h



Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
600/70R28	161/161	A8/B	R-1W	DW18L DW20B W18L	591	1551	4625	280	52.5	TL
600/70R30	152	D	R-1W	DW18L DW20B W18L	591	1602	3550	160	52.5	TL
	158	D	R-1W	DW18L DW20B W18L	591	1602	4250	240	52.5	TL
620/70R42	172	D	R-1W	DW18L W18L DW20B	625	1935	6300	320	58	TL
650/85R38	173/176	D/A8	R-1W	DW20B DW21B DW23B	645	2071	6500	240	65	TL
600/70R34	160/163	D/A8	R-1W	DW18L DW20B W18L	601	1704	4500	240	52	TL
650/60R34	159/162	D/A8	R-1W	DW20B DW21B DW23B	645	1644	4375	240	52	TL
710/55R30	153/156	D/A8	R-1W	DW23B DW24B	706	1544	3650	160	51	TL
710/75R42	181/184	D/A8	R-1W	DW20B DW21B DW23B DW24B DW25B	706	2133	8250	320	63	TL
800/70R38	178/181	D/A8	R-1W	DW25B DW27B	798	2085	7500	240	62	TL



AGRI HARVEST BLA09

- ✓ Carry up to 40% more load at the same pressure versus non-VF radial tire of the same size
- ✓ Wide footprint creating broader contact area with the soil
- ✓ Reinforced structure resistant to punctures and cuts



Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
VF 520/85R42 CFO	177	A8	R-1W	DW18L	516	1951	7300	280	52	TL
VF 600/60R30	162	D	R-1W	DW20B DW21B	597	1482	4750	200	52	TL
VF 710/60R38	178	D	R-1W	DW24B DW25B	708	1817	7500	280	60	TL
VF 750/75R46	191	D	R-1W	DW25B	742	2294	10900	320	70	TL
VF 800/65R32 CFO	183	A8	R-2	DW27B DW28B	796	1853	8750	240	70	TL
VF 900/60R32	191	A8	R-1W	DW30B	891	1893	10900	280	56	TL
VF 900/60R38	193	A8	R-1W	DW30B	891	2045	11500	280	58	TL
VF 900/65R46	199	D	R-1W	DW30B	891	2338	13600	360	69	TL



BLA01

- ✓ Deep lugs, low slip and optimized rubber compounds help to reduce wear for exceptional long tire life
- ✓ Good self-cleaning properties help to keep the tread pattern free of mud, resulting in less slip, even in difficult conditions



Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
380/90R46	157/157	A8/B	R-1W	W11 W12 W13	380	1852	4125	360	45	TL
320/90R46	146/143	A8/B	R-1	W9 W10 W11	319	1744	3000	320	37	TL



BLA08

- ✓ Deep lugs provide excellent traction, better directional stability and a high level of control
- ✓ An extra-strong but super-flexible casing, which offers a large footprint and surprising ride comfort, has excellent durability to carry extra-heavy loads



Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
320/90R42	147/147	A8/B	R-1	W9 W10 W11	319	1643	3075	400	37	TL
380/90R50	160/157	A8/B	R-1W	W11 W12 W13	380	1954	4500	400	48	TL



BLAF1

- ✓ Solid rounded shoulders increases maneuverability and reduces scrub
- ✓ Extremely economical thanks to excellent traction and low-wear tread compound
- ✓ Even distribution of ground pressure to minimize rutting and soil damage



Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
600/50R22.5 IMP	159	D	I-3	AG20.00	611	1172	4375	400	25	TL
650/65R30.5 IMP	176	D	I-3	AG20.00	645	1621	7100	400	32	TL
850/50R30.5 IMP	182	D	I-3	AG28.00	862	1625	8500	400	32	TL



BLF01

- ✓ With a large contact patch, this tire offers max flotation and soil protection
- ✓ Solid rounded shoulders for greater resistance to irregular wear, reduced scrub and improved maneuverability
- ✓ Steel belted design increases load capacity and resistance to impacts



Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
400/45R15 IMP	140	D	I-3	13LB	404	741	5520	550	20	TL
500/50R17 IMP	149	D	I-3	16	503	932	3250	500	15	TL
500/45R22.5 IMP	146	D	I-3	AG16.00	503	1022	3000	400	21	TL
500/60R22.5 IMP	155	D	I-3	AG16.00	503	1172	3875	400	18	TL
560/45R22.5 IMP	152	D	I-3	AG16.00	543	1076	3550	400	18	TL
560/60R22.5 IMP	165	D	I-3	AG16.00	543	1244	5150	500	18	TL
580/65R22.5 IMP	166	D	I-3	AG18.00	577	1326	5300	400	21	TL
600/50R22.5 IMP	163	D	I-3	AG18.00	591	1172	4875	500	21	TL
600/55R26.5 IMP	165	D	I-3	AG20.00	591	1333	5150	400	20	TL
650/55R26.5 IMP	169	D	I-3	AG20.00	645	1389	5800	400	24	TL
650/65R26.5 IMP	174	D	I-3	AG20.00	645	1519	6700	400	24	TL
710/45R22.5 IMP	165	D	I-3	AG22.00	706	1212	5150	400	25	TL
710/50R26.5 IMP	170	D	I-3	AG24.00	727	1383	6000	400	24	TL
710/50R30.5 IMP	173	D	I-3	AG24.00	727	1485	6500	400	26	TL
750/45R26.5 IMP	170	D	I-3	AG24.00	754	1349	6000	400	25	TL
750/60R30.5 IMP	181	D	I-3	AG24.00	754	1675	8250	400	26	TL
800/45R26.5 IMP	174	D	I-3	AG26.00	808	1393	6700	400	26	TL
800/45R30.5 IMP	176	D	I-3	AG26.00	808	1495	7100	400	26	TL
850/50R30.5 IMP	182	D	I-3	AG28.00	842	1625	8500	400	27	TL



BLA04

- ✓ Extra-deep 40° lugs provide impressive traction and excellent directional control
- ✓ Reinforced centreline undertread for tread penetration resistance



Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
280/80R20 IND	133/133	A8/B	R-4	W8 W9 W10	282	956	2060	400	29	TL
400/70R20 IND	149/149	A8/B	R-4	12SDC 13 13SDC 14	404	1068	3250	400	33	TL
460/70R24 IND	159/159	A8/B	R-4	DW14L DW15L DW16L	455	1254	4375	400	36	TL
500/70R24 IND	164/164	A8/B	R-4	DW16L DW15L	503	1310	5000	400	39	TL
500/85R24 IMP	158/171	A8/A8	I-3	W15L DW15L DW16L	500	1445	/heel)6150	280	37.5	TL
540/70R24 IND	168/168	A8/B	R-4	DW16L DW18L	540	1366	5600	400	36	TL



BLA06

- ✓ Extremely economical thanks to excellent traction and low-wear tread compound
- ✓ Outstanding grip on hard surfaces due to new block tread pattern designed for industrial applications



Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
500/70R24 IND	164/164	A8/B	R-4	DW16L DW15L	503	1310	5000	400	28	TL
400/70R18 IND	147/147	A8/B	R-4	12 12SDC 13 13.00	404	1017	3075	400	23	TL
400/70R20 IND	149/149	A8/B	R-4	12SDC 13 13SDC 14	404	1068	3250	400	23	TL



LL309

- ✓ Tread pattern with very good traction and self-cleaning properties
- ✓ Ability to withstand heavy loads



Size	Ply Rating	TRA Code	RIM	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
405/70-24 (16/70-24)	14	MPT	13(SDC)	410	1175	5600	450	25	TL



BLT03

- ✓ Suitable for trailer axle
- ✓ Specially used for agriculture



Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
385/55R19.5	156	D	/	12.25	386	919	4000	900	12.5	TL
435/50R19.5	160	D	/	14.00	438	931	4500	900	12.5	TL
445/45R19.5	160	D	/	15.00	446	895	4500	900	15.5	TL



BL606

- ✓ Extra wide tread grooves ensure superior water dispersal
- ✓ Suitable for trailer axle



Size	Load Index	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
425/65R22.5	165	D	/	13.00	430	1124	5150	900	17.5	TL
445/65R22.5	169	D	/	14.00	444	1150	5800	900	18	TL



BBAF2

- ✓ Shallow tread depth provides excellent heat dissipation
- ✓ Rib design provides excellent steering stability



Size	Ply Rating	Load index	Speed symbols	RIM	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	TRA Code
12.5/80-15.3 IMP	14	142	A6	9.00	308	900	2650	430	9	I-1
10.0/75-15.3 IMP	14	130	A6	9.00	264	780	1900	550	8	I-1



BBAF1E

- ✓ Optimized contour design with lighter tire weight, which brings better purchasing economics
- ✓ Puncture resistant
- ✓ Low ground pressure helps protect crops and increase yield



Size	Ply Rating	TRA Code	RIM	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
400/60-15.5 IMP	16	I-3	AG13.00	404	874	3150	400	15	TL

Good quality OTR tires providing a better road contact for improved driving comfort and lower fuel consumption.

Flexible tires, which are strong and capable of effectively dealing with shocks from the road surface.

These are the properties offered by our wide range of radial OTR tires.

Barkley's diagonal tires ensure high vehicle stability and higher resistance against damage to the tire's side walls.

**OTR/
OFF-THE-ROAD**





LOADERS & DOZERS

BXL MASTER PRO

- ✓ Optimized pattern angle provides superior traction compare with previous products
- ✓ Larger center blocks bring even wear
- ✓ Robust shoulder and enhanced sidewall offer great resistance to damage and aggression

NEW



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
15.5R25	★★	A2	E-3/L-3	12.00/1.3	390	1274	7100	650	24	TL
17.5R25	★★	A2	E-3/L-3	14.00/1.5	444	1346	8500	650	27	TL
20.5R25	★★	A2	E-3/L-3	17.00/2.0	520	1484	11500	650	30	TL
23.5R25	★★	A2	L-3	19.50/2.5	610	1604	14500	650	33	TL
26.5R25	★★	A2	L-3	22.00/3.0	687	1732	18500	650	36	TL
29.5R25	★★	A2	L-3	25.00/3.5	749	1862	22400	650	42	TL



LOADERS & DOZERS

BXL PRO

- ✓ Non-directional pattern for outstanding traction
- ✓ Aggressive tread design for excellent handling and lateral adhesion
- ✓ Optimized contour design with lighter tire weight compared with BXL MASTER PRO, which brings better purchasing economics

NEW



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
23.5R25	★★	A2	L-3	19.50/2.5	590	1605	14500	650	32	TL



LOADERS & DOZERS

BLB01

- ✓ Optimized tread compound for extended wear and endurance
- ✓ Wide aggressive tread design for excellent handling and lateral adhesion
- ✓ Maximized sidewall reinforcement protects against cutting and abrasion in the toughest applications



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
17.5R25	★★	A2	E-3/L-3	14.00/1.5	445	1348	8500	650	27	TL
20.5R25	★★	A2	E-3/L-3	17.00/2.0	521	1493	11500	650	30	TL
23.5R25	★★	A2	L-3	19.50/2.5	597	1617	14500	650	33	TL
26.5R25	★★	A2	L-3	22.00/3.0	673	1750	18500	650	36	TL
29.5R25	★★	A2	L-3	25.00/3.5	749	1874	22400	650	39	TL



LOADERS & DOZERS

BLB05S

- ✓ Excellent lateral grip on soft terrain due to self-cleaning tread pattern
- ✓ Excellent traction on rocky, gravel and packed earth surface in mines, quarries and construction sites
- ✓ Special styrene-butadiene rubber tread compound improves wearing and reduces heat generation



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
26.5R25	★★	A2	L-3	22.00/3.0	673	1750	18500	650	44	TL
29.5R25	★★	A2	L-3	25.00/3.5	749	1874	22400	650	44	TL
750/65R25	★★	A2	E-3/L-3	24.00/3.0	754	1611	18500	625	45	TL
850/65R25	★★	A2	E-3/L-3	27.00/3.5	852	1741	23000	625	46	TL



LOADERS & DOZERS

BXS MASTER PRO

NEW



- ✓ Protective band on the shoulder/sidewall interface provide excellent protection against accidental damage
- ✓ Tread blocks with multiple sipes and offset shoulder blocks ensure excellent traction in mud and on snow and ice
- ✓ The open shoulder pattern, is the foundation for the excellent self cleaning in snow or mud

Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
14.00R24	★	A8/A2	G-2/L-2	8.00TG	362	1348	3650	375	23	TL
17.5R25	★★	A2	E-2/L-2	14.00/1.5	444	1346	8500	650	27	TL
20.5R25	★★	A2	E-2/L-2	17.00/2.0	520	1476	11500	650	31	TL
23.5R25	★★	A2	E-2/L-2	19.50/2.5	610	1594	14500	650	34	TL



LOADERS & DOZERS

BLS09

- ✓ Exceptional maneuverability on ice and snow
- ✓ Optimized tread pattern for maximum traction
- ✓ Special snow tread compound enhances grip



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
15.5R25	★★	A2	E-2/L-2	12.00/1.3	394	1278	7100	650	24	TL
17.5R25	★★	A2	E-2/L-2	14.00/1.5	445	1348	8500	650	27	TL
20.5R25	★★	A2	E-2/L-2	17.00/2.0	521	1493	11500	650	30	TL
23.5R25	★★	A2	E-2/L-2	19.50/2.5	597	1617	14500	650	32	TL
26.5R25	★★	A2	E-2/L-2	22.00/3.0	673	1750	18500	650	35	TL



LOADERS & DOZERS

BXG MASTER PRO

NEW



- ✓ Optimized pattern design provides superior traction and flotation
- ✓ Non-directional tread pattern simplified tire installation
- ✓ Cut-resistant tread design for even wear

Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
17.5R25	★★	A2/B	G-2/L-2	14.00/1.5	444	1346	5450	525	27	TL



LOADERS & DOZERS

BLGRADER PRO+

NEW



- ✓ Non-directional tread pattern delivers exceptional traction and stability
- ✓ Enhanced sidewall intersection offers improved resistance to damage
- ✓ Unique tread compound offers excellent wear life

Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
14.00R24	★	A8/A2	G-2/L-2	8.00TG	351	1347	3650	375	26	TL



LOADERS & DOZERS

BXL TRAC PRO

- ✓ Optimized pattern design provides superior traction
- ✓ Non-directional tread pattern simplified tire installation
- ✓ Robust shoulder rib offers added sidewall protection

NEW



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
17.5R25	★★	A2	L-5	14.00/1.5	451	1400	8500	650	64	TL
20.5R25	★★	A2	L-5	17.00/2.0	520	1534	11500	650	72	TL
23.5R25	★★	A2	L-5	19.50/2.5	612	1660	14500	650	78	TL
26.5R25	★★	A2	L-5	22.00/3.0	692	1795	18500	650	87	TL
29.5R25	★★	A2	L-5	25.00/3.5	754	1900	22400	650	94	TL



LOADERS & DOZERS

BXL PROTECT PRO

- ✓ Deeper tread pattern provides longer wear life compare with previous products
- ✓ Strong tread pattern improves tire cut resistance in severe working conditions
- ✓ Rugged shoulder rib offers added sidewall protection

NEW



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
17.5R25	★★	A2	L-5	14.00/1.5	451	1400	8500	650	67	TL
20.5R25	★★	A2	L-5	17.00/2.0	520	1542	11500	650	79	TL
23.5R25	★★	A2	L-5	19.50/2.5	612	1672	14500	650	87	TL
26.5R25	★★	A2	L-5	22.00/3.0	692	1795	18500	650	96	TL
29.5R25	★★	A2	L-5	25.00/3.5	754	1920	22400	650	104	TL



LOADERS & DOZERS

BLB07S+

- ✓ Directional tread pattern enhances traction in mud and soft conditions
- ✓ Excellent performance in severe rock application
- ✓ Deep tread depth provides outstanding wearing life



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
20.5R25	★★	A2	L-5	17.00/2.0	521	1548	11500	650	70	TL
23.5R25	★★	A2	L-5	19.50/2.5	597	1673	14500	650	76	TL
26.5R25	★★	A2	L-5	22.00/3.0	673	1798	18500	650	85	TL
29.5R25	★★	A2	L-5	25.00/3.5	747	1895	22400	650	91	TL



LOADERS & DOZERS

BLB06S+

- ✓ Combined smooth and lug tread pattern for enhanced cut resistance and traction
- ✓ High-tensile steel belt package for enhanced impact resistance
- ✓ Deep tread depth for extra grip and long wear



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
17.5R25	★★	A2	L-5	14.00/1.5	445	1399	8500	650	62.5	TL
20.5R25	★★	A2	L-5	17.00/2.0	521	1548	11500	650	70	TL
23.5R25	★★	A2	L-5	19.50/2.5	597	1673	14500	650	76	TL
26.5R25	★★	A2	L-5	22.00/3.0	673	1798	18500	650	85	TL
29.5R25	★★	A2	L-5	25.00/3.5	747	1895	22400	650	91	TL



LOADERS & DOZERS

BXA PROTO

- ✓ Self-cleaning pattern design improves tire traction
- ✓ Rugged shoulder rib offers added sidewall protection
- ✓ Larger footprint with lower ground contact pressure bring better stability and excellent mobility

NEW



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
29.5R25	★★	A2	L-3	25.00/3.5	749	1856	22400	650	43	TL
650/65R25	★★	A2	E-3/L-3	19.50/2.5	642	1490	14000	625	39.5	TL
750/65R25	★★	A2	E-3/L-3	24.00/3.0	754	1602	18500	625	43	TL



ADT & SCRAPER

BXA PROTO

- ✓ Self-cleaning pattern design improves tire traction
- ✓ Rugged shoulder rib offers added sidewall protection
- ✓ Larger footprint with lower ground contact pressure bring better stability and excellent mobility

NEW



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
29.5R25	★★	B	E-3	25.00/3.5	749	1856	14000	525	43	TL
750/65R25	★★	B	E-3	24.00/3.0	754	1602	10600	475	43	TL



LOADERS & DOZERS

BLA06

- ✓ Nylon casing provides superior riding comfort
- ✓ Steel belted tread design prevents tire puncture
- ✓ Special tread compound enhances tread wearing



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
405/70R18	141/153	B/A2	/	13.00	407	1025	2575	380	23	TL
405/70R20	143/155	B/A2	/	13.00	407	1076	2725	380	23	TL



ADT & SCRAPER

BXA MASTER PRO

- ✓ Massive tread blocks ,good water -ejection and mud-ejection, excellent tractive performance especially on the muddy surface
- ✓ Rugged shoulder rib offers added sidewall protection
- ✓ The specially engineered tread design reduces vibrations for a smooth, comfortable ride

NEW



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
23.5R25	★★	B	E-4	19.50/2.5	596	1622	9250	525	54	TL
26.5R25	★★	B	E-4	22.00/3.0	687	1744	11500	525	59	TL
29.5R25	★★	B	E-4	25.00/3.5	749	1868	14000	525	64	TL



ADT & SCRAPER

BLM06S

- ✓ Optimized tread compound for extended wear and endurance
- ✓ Enhanced radial construction provides superior flotation and stability
- ✓ Tread pattern designed to deliver long tire life and great traction



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
20.5R25	★★	B	E-4	17.00/2.0	521	1493	7300	525	50	TL
23.5R25	★★	B	E-4	19.50/2.5	597	1673	9250	525	50	TL
26.5R25	★★	B	E-4	22.00/3.0	673	1798	11500	525	55	TL
29.5R25	★★	B	E-4	25.00/3.5	749	1921	14000	525	60	TL



MOBILE CRANE

BXC MASTER PRO

- ✓ Improvement in irregular wear patterns so that the crane generates fewer vibrations
- ✓ More rigid rubber compound in the tread
- ✓ Tread design offers high-speed capability while minimizing fuel consumption

NEW


Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
385/95R24	★★★	F	E-2	10.00W	379	1362	6000	900	23	TT
385/95R25	★★★	F	E-2	10.00/1.5	379	1362	6000	900	23	TL
445/95R25	★★★	F	E-2	11.25/2.0	435	1472	6700	900	25	TL
525/80R25	★★★	F	E-2	17.00/2.0	522	1482	7100	700	30	TL



SAND

BXF MASTER PRO

- ✓ Multi-rocks with staggered tread blocks provides high mobility
- ✓ Optimized tread designed for desert and soft ground
- ✓ Strong casing provides heavy load at low inflation pressure

NEW


Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
24R20.5	★	F	E-7	18	600	1370	7100	600	20.5	TL



MOBILE CRANE

CRANE PROTO

- ✓ Optimum casing design ensures even contact distribution which leads even wearing
- ✓ The newly developed compound leads to a remarkable increase in life

NEW


Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
385/95R25	★★★	E	E-2	10.00/1.5	379	1362	6000	900	21	TL



RIGID DUMP TRUCKS

BLDUMP 44+

- ✓ Wide and big transverse grooves deliver better cut resistance for short one-way distance application
- ✓ Outstanding tire life and exceptional resistance to aggression
- ✓ Standard tread compound design, balancing cutting and heat resistance

NEW



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
14.00R24	★★★	B	E-3	10.00W	378	1370	5800	700	29.5	TT



RIGID DUMP TRUCKS

BLDUMP 68

- ✓ Unique compoud for enhanced cutting resistance and long tread life
- ✓ Block pattern for effective heat dissipation and long one-way distance application
- ✓ Standard tread compound design, balancing cutting and heat resistance

NEW



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
14.00R25	★★★	B	E-3	10.00/2.0	361	1354	5800	700	27	TT



RIGID DUMP TRUCKS

BLDUMP 66+

- ✓ Wide and big transverse grooves deliver outstanding tire life and exceptional resistance to aggression
- ✓ New bead area and more robust architecture increase more load capacity
- ✓ Diversified tread compounds meet performance requirements in different scenarios

NEW



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
14.00R25	★★★	B	E-3	10.00/2.0	361	1354	5800	700	27	TT/TL



RIGID DUMP TRUCKS

BLDUMP 68+

- ✓ Unique compoud for enhanced cutting resistance
- ✓ Tough casing construction for enhanced impact and cut resistance support
- ✓ Deep lug pattern tread delivers longer service life and better traction capacity

NEW



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
14.00R25	★★★	B	E-4	10.00/2.0	361	1374	5800	700	37	TT/TL
16.00R25	★★★	B	E-4	11.25/2.0	431	1528	8000	800	42	TT/TL



RIGID DUMP TRUCKS

BLDUMP 33+

- ✓ Reinforced carcass for higher load capacity and explosion-proof performance
- ✓ Aggressive tread pattern for enhanced cutting and slipping resistance
- ✓ Diversified tread compounds meet performance requirements in different scenarios

NEW



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
16.00R25	★★★	B	E-3	11.25/2.0	448	1492	8000	800	27	TT/TL



RIGID DUMP TRUCKS

BLDUMP 69+

- ✓ Proper horizontal tread pattern balances cut resistance and heat generation for medium one-way distance application
- ✓ Diversified tread compounds meet performance requirements in different scenarios

NEW



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
14.00R25	★★★	B	E-3	10.00/2.0	361	1354	5800	700	27	TT/TL



RIGID DUMP TRUCKS

BLDUMP 36+

- ✓ Self-cleaning pattern design improves tire traction and adhesion
- ✓ Reinforced carcass for higher load capacity and explosion-proof performance
- ✓ Block pattern for effective heat dissipation and long one-way distance application

NEW



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
480/95R29	★★★	B	E-3	13.00/2.5	490	1634	10500	800	32	TT/TL



RIGID DUMP TRUCKS

BLDUMP 98+

- ✓ Deeper tread depth delivers longer life
- ✓ Reinforced carcass for higher load capacity and explosion-proof performance
- ✓ Aggressive tread pattern for enhanced cutting and slipping resistance

NEW



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
16.00R25	★★★	B	E-3	11.25/2.0	442	1492	8000	800	31	TT/TL
480/95R29	★★★	B	E-3	13.00/2.5	490	1634	10500	800	32	TT/TL



RIGID DUMP TRUCKS

BLDUMP TRAC

- ✓ Special tread compound for exceptional wear and cut resistance
- ✓ Self-cleaning tread design provides good traction and stability on the soft and muddy ground
- ✓ Deeper tread depth ensures exceptional tread wear



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
18.00R25	★★	B	E-4	13.00/2.5	498	1673	9250	700	46	TL
18.00R25	★★★	B	E-4	13.00/2.5	498	1673	10300	800	46	TL
24.00R35	★★	B	E-4	17.00/3.5	658	2164	18500	700	66	TL
27.00R49	★★	B	E-4	19.50/4.0	730	2698	27250	700	76	TL



RIGID DUMP TRUCKS

BXD MASTER PRO

- ✓ Optimized tread pattern design and cooling vents provide heat resistance
- ✓ Deeper tread depth ensures exceptional tread wear
- ✓ Multiple tread compound options target specific site requirements



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
46/90R57	★★	B	E-4	29.00/6.0	1153	3579	63000	700	95	TL



RIGID DUMP TRUCKS

BLROCK PROTO

- ✓ New optimized sculpture with cooling vents
- ✓ Deep tread combined with sturdy shoulder and sidewall provide excellent traction and stability
- ✓ Multiple tread compound options target specific site requirements



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
27.00R49	★★	B	E-4	19.50/4.0	730	2698	27250	700	76	TL
33.00R51	★★	B	E-4	24.00/5.0	909	3048	38750	700	87	TL



RIGID DUMP TRUCKS

BLB02S

- ✓ Special compounds for exceptional wear and cut resistance
- ✓ Self-cleaning tread design provides good traction and stability on the soft and muddy ground
- ✓ Deeper tread depth ensures exceptional tread wear



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
18.00R33	★★	B	E-4	13.00/2.5	498	1877	10900	700	52	TL



UNDERGROUND MINE

LHD MASTER PRO

- ✓ Strengthened grip with a large ground contact area
- ✓ Robust shoulders with sidewall protection
- ✓ Improved tire life in the harshest conditions thanks to optimized tread compound
- ✓ Wear indicators in tire tread facilitate tread wear assessment

NEW

Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
12.00R24	★★	A2	L-5S	8.50V	315	1275	6900	825	53	TT
14.00R24	★★★	A2	L-5S	10.00W	375	1400	10000	950	58	TT
17.5R25	★★	A2	L-5S	14.00/1.5	445	1400	8500	650	78	TT/TL
18.00R25	★★	A2	L-5S	13.00/2.5	500	1675	16000	825	83	TL
26.5R25	★★	A2	L-5S	22.00/3.0	685	1778	18500	650	96	TL



UNDERGROUND MINE

LHD PROTO

- ✓ Robust shoulders with sidewall protection
- ✓ Improved tire life in the harshest conditions thanks to optimized tread compound

NEW

Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
17.5R25	★★	A2	L-5S	14.00/1.5	445	1390	8500	650	73	TT/TL



HEAVY TRUCK

BXF PROTO

- ✓ Directional pattern designed to deliver long tire life and even wear
- ✓ Nylon casing with supple sidewall provides superior riding comfort
- ✓ Optimized steel belted ensure anti-puncture performance

NEW

Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
425/85R21	156	D	—	12.00/1.5	425	1265	4000	550	24	TT



HEAVY TRUCK

BXF EXTREME

- ✓ Unique pattern design ensures the product has excellent off-road performance
- ✓ Open tire shoulder is conducive to heat dissipation

NEW

Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
16.00R20NHS	★★	B	E-2	11.25/2.0	447	1330	6900	650	25	TT



HEAVY TRUCK

BLM05

- ✓ Unique pattern design ensures the product has excellent off-road performance
- ✓ Open tire shoulder is conducive to heat dissipation



Size	Load Index /Star Rating	Speed Symbols	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
16.00R20NHS	★★	B	E-2	11.25/2.0	447	1318	6900	650	20	TT



ROLLER

LL308

- ✓ Unique tread pattern design provides optimal passability
- ✓ Specially designed tread compound ensures excellent cutting resistance



Size	Ply Rating	TRA Code	Rim	Section Width (mm)	Overall Diameter (mm)	Load Capacity (kg)	Inflation Pressure (kPa)	Tread Depth (mm)	Type
23.1-26	12	E-7	DW20	595	1500	5150	200	15	TT/TL
	16	E-7	DW20	595	1500	6150	260	15	TT/TL